

ANYSHOP PRIME

Power and Style at Your Space™

- High-End POS System with Alluring Style
- Robust Performance with the 4th Generation Intel® Processors
- Bezel-free True-Flat 15" and 17" LED LCD Display with PCAP Touch
- Tool-less Design for Rapid installation and Easy Maintenance
- Color Customization

Specifications

System

CPU	Q3	Intel® Core™ i3-4100M Processor (3M Cache, 2.50 GHz) / Fanless
Chipset	Qs	Intel® HM76 or HM87
Storage	Qs	SATA 3 (6Gb/s) 2.5 inch SSD 64GB, Support AHCI
Memory	Qs	2GB Standard (Max. 16GB), DDR3L with 1066 or 1333 MT/s / Socket 1 x SODIMM (Max. 2 Optional)
RAID	Qs	RAID 0,1 support
Graphics Controller		Integrated Intel GMA HD
Audio		2 x 0.8W Stereo Speaker

LCD Display

Size/Type	15" TFT LED Backlight 17" TFT LED Backlight	
Resolution	1024 x 768	1280 x 1024
Luminance	250 cd/m ² (typ.)	300 cd/m ² (typ.)
Touch Screen		
Type	Project Capacitive Touch	
Controller Interface	USB Interface	

I/O Interface

Display Port	1 x VGA	
USB Port	Qs	8 (Rear 6 = USB 3.0 x 4 Ports, USB 2.0 x 2 Ports, Side 2 = USB 2.0 x 2 Ports)
J19	8 (Rear 6 = USB 3.0 x 1 Port, USB 2.0 x 5 Ports, Side 2 = USB 2.0 x 2 Ports)	
PS/2 Port	1	
Serial Port	3 (COM 1 ~ 3 with 5V/12V power output on 9pins)	

Ethernet Port 2 x RJ-45
Audio 1 x Line-out, 1 x Mic-in
Power DC-IN Qs 1 (3pins connector)
Power Requirement
Adapter Input Qs Adaptor 24V, 5A

OS Support

OS Windows 7, Windows 8.1, POS Ready 7

Mechanical & Environmental

Operating Temperature 0°C ~ 50°C at 10% ~ 90% humidity
Storage Temperature -20°C ~ 80°C at 10% ~ 90% humidity
Relative humidity 10% to 90%, non-condensing
Dimensions (W x H x D) 364 x 382 x 344(mm), 14.3 x 15 x 13.5(inch) 392 x 410 x 346(mm), 15.4 x 16.1 x 13.6(inch)
Net Weight 7,500g
Packing Dimension (W x H x D) 460 x 480 x 460(mm), 18.1 x 18.8 x 18.1(inch) 460 x 480 x 500(mm), 18.1 x 18.8 x 19.6(inch)
Packing Weight 10,000g
Qualification CE, FCC, KC

Optional Configuration

Touch Screen 5-wired Resistive Touch Screen
Storage 2.5 inch SSD 128GB
2.5 inch HDD 500GB
2.5 inch HDD 1TB
2nd 2.5 inch SSD 64GB
2nd 2.5 inch SSD 128GB
2nd 2.5 inch HDD 500GB
2nd 2.5 inch HDD 1TB
I/O Expansion 1 x Cash Drawer Port (RJ11 6pins)
Customer Display(CDP) VFD (20 columns x 2 lines)
Dual Display 9.7" 2nd LCD (1024 x 768 resolution)
12.1" 2nd LCD (1024 x 768 resolution)

15" 2nd LCD (1024 x 768 resolution)

Magnetic Stripe Reader MSR: Comply with ISO 7811, Support 1 & 2 & 3 track

Smart Card Reader SCR: EMV level 1, 2

Dallas Dallas I-button Reader

Battery Smart Battery: 3S1P 2050mAh

Smart Battery: 4S1P 2050mAh

Color Custom Colors Available