

ANYSHOP e2

Stylish, Reliable and Affordable

- Stylish Design
- Performance / Energy-Efficient Intel® Processors
- Secondary HDD or SSD Drive
- Multiple I/O Ports
- System Expandability
- Optional Color Case
- Easy Installation and Maintenance
- Onboard UPS technology to Prevent Data Loss from Power Outages

Specifications

CPU uPGA988 for 2nd and 3rd Generation Intel® Core™ i7/i5/i3, Intel® Pentium, Intel® Celeron Processors

Chipset Intel HM76 Intel HM87

Storage SATA 3 (6Gb/s) 2.5 inch HDD or SSD (Max. 2 Optional), Support AHCI
(SSD: 64GB or 32GB / HDD: 320GB)

Memory DDR3-1600MHz SODIMM Default 2GB (MAX. 8GB)

Graphic Integrated Intel GFX

AMT Support iAMT 8.0 -

Display

Resolution 15" LED Backlight TFT-LCD 250 cd/m² (1024 x 768 resolution)

Touch screen 5-wired Resistive Touch

Internal I/O

USB 3 Ports (reserved for touch controller, SCR EMV card, camera and MSR controller)

Serial port COM 5 (reserved for cash drawer port) & COM 6 (reserved for MSR)

Display port LVDS or VGA & COM 4 (reserved for CDP)

Extension slot Mini PCIe

Primary display 24bit LVDS

External I/O

USB Rear 6 (USB 3.0 x 4 ports, USB 2.0 x 2 ports) Rear 4 (USB 3.0 x 2 ports, USB 2.0 x 2 ports)

PS/2 1 Port (reserved for Keyboard & Mouse)

Serial port COM 1 ~ 3 with 5V/12V power output on 9pin

LAN Gigabit Ethernet x 2 ports

1x Intel Gigabit LAN with iAMT 8.0(Intel 82579LM)

1x Intel Gigabit LAN with (Intel 82583V) 1 port x Intel Gigabit LAN with (Intel 82583V)

Audio Realtek ALC 892 / Line-out, Mic-in

Display port VGA x 1 port

Options

MSR Comply with ISO 7811, Support 1 & 2 & 3 track

Speaker 2 x 0.8W (Stereo)

Side USB 4 Ports (USB 2.0 x 4 ports)

SCR EMV level 1

Dallas Dallas I-button reader

Back up battery Smart battery (supports up to 1 packs)

Customer display VFD type (20 x 2)

2nd LCD 9.7", 12.1" LCD (1024 x 768 resolution)

2nd Storage 2nd 2.5 inch HDD / SSD storage

Cash drawer port 1 Port

Parallel port 1 Port

WiFi Mini PCIe for wireless LAN

Operating Temperature 0 °C ~ 40 °C at 10% ~ 80% humidity

Storage Temperature -20 °C ~ 60 °C at 10% ~ 80% humidity

Certification CE, FCC, KC

Power Adaptor 24V, 6A

OS Support Windows 7, Windows 8, POS Ready 7

Dimension (W x H x D) 365 x 305 x 385(mm), 14.3 x 12 x 15.1(inch)

ANYSHOP® e2 D25

CPU Intel Atom processor D2550 (1MB Cache, 1.86 GHz, Dual Core for Cedarview-D)

Chipset Intel NM10

Storage SATA 2 (3Gb/s) 2.5 inch HDD or SSD (Max. 2 Optional), Support AHCI

(SSD: 64GB or 32GB / HDD: 320GB)

Memory DDR3-1066MHz SODIMM 2GB (MAX. 4GB)

Graphic Integrated Intel GMA HD 3650

Display

Resolution 15" LED Backlight TFT-LCD 250 cd/m² (1024 x 768 resolution)

Touch screen 5-wired Resistive Touch

Internal I/O

USB 3 Ports (reserved for touch controller, SCR EMV card, camera and MSR controller)

Serial port COM 5 (reserved for cash drawer port) & COM 6 (reserved for MSR)

Display port VGA & COM 4 (reserved for CDP)

Extension slot Mini PCIe

Primary display 24bit LVDS

External I/O

USB Rear 4 (USB 2.0 x 4 ports)

PS/2 1 Port (reserved for Keyboard & Mouse)

Serial port COM 1 ~ 3 with 5V/12V power output on 9pin

LAN Realtek RTL 8111E Ethernet Controller

Audio Realtek ALC 892 / Line-out, Mic-in

Display port VGA x 1 port

Options

MSR Comply with ISO 7811, Support 1 & 2 & 3 track

Speaker 2 x 0.8W (Stereo)

Side USB 4 Ports (USB 2.0 x 4 ports)

SCR EMV level 1

Dallas Dallas I-button reader

Back up battery Smart battery (supports up to 1 packs)

Customer display VFD type (20 x 2)

2nd LCD 9.7", 12.1" LCD (1024 x 768 resolution)

2nd Storage 2nd 2.5 inch HDD / SSD storage

Cash drawer port 1 Port

Parallel port 1 Port

WiFi Mini PCIe for wireless LAN

Operating Temperature 0 °C ~ 40 °C at 10% ~ 80% humidity

Storage Temperature -20 °C ~ 60 °C at 10% ~ 80% humidity

Certification CE, FCC, KC

Power Adaptor 12V, 5A

OS Support Windows XP/Vista, Windows 7, POS Ready 2009/7

Dimension (W x H x D) 365 x 305 x 385(mm), 14.3 x 12 x 15.1(inch)