

POSBANK Touch Monitor

Affordable, Versatile and Durable

- 15" LCD Display (1024 x 768, Resistive Touch)
- 17" LCD Display (1280 x 1024, Projective Capacitive Touch)
- Eco-friendly, Low Power LED Backlight Display
- Compact Space-Saving Design
- Optional Multi-reader (MSR, SCR, I-Button)

Specifications

LCD Display

Size/Type 15" TFT LED Backlight 17" TFT LED Backlight

Resolution 1024 x 768 Resolution 1280 x 1024 Resolution

Luminance LCD panel : 250cd/m² (typ.) LCD panel : 300cd/m² (typ.)

Contrast Ratio 500 : 1 (Typ.) 1000 : 1 (Typ.)

View Angle (U/D/R/L) 80°/80°/80°/80° (Typ.) 85°/85°/80°/80° (Typ.)

Touch Screen

Type 5-wired Resistive Touch Projected Capacitive Touch

Controller Interface USB Interface

I/O Interface

VGA 1

USB (A Type) 2

USB (B Type) 1

Ethernet Port 1 (RJ-45 for MSR)

Audio 1

Power

Adapter Input Adaptor 12V, 3A

Mechanical & Environmental

Dimensions (W x H x D) 364 x 345 x 217(mm), 14.3 x 13.6 x 8.5(inch) 392 x 376 x 217(mm), 15.4 x 14.8 x 8.5(inch)

Net Weight 5600g

Packing Dimension (W x H x D) 420 x 325 x 455(mm), 16.5 x 12.7 x 17.9(inch)

Packing Weight 7400g

Certification CE, FCC, KC

*Specifications may change without prior notice.

Optional Configuration

MSR Comply with ISO 7811, Support 1& 2 & 3 track