

SLK-T42

SPECIFICATIONS

PRINTING

- METHOD : Direct Thermal
- SPEED : 200mm/sec
- WIDTH : 54mm(432Dots/Line)
- RESOLUTION : 203 DPI
- DIRECTION : Unidirectional with Friction Feed

CHARACTER SET

- ALPHA NUMERIC CHARACTER : 95
- EXTENDED GRAPHIC : 128 x 18 Page (1 space page)
- INTERNATIONAL CHARACTER : 14

BARCODE

- 1D : EAN-8, EAN-13, Code 39, Code 93, Code 128, ITF, UPC-A, UPC-E, Codabar
- 2D : PDF 417, QR code

CHARACTER PER LINE

- Font A(12x24) : 36 columns
- Font B(9x17) : 48 columns

DOT

- PITCH : 0.125mm x 0.125mm

PAPER SPECIFICATION

PAPER

- TYPE : Thermal Paper
- WIDTH : 59 mm \pm 0.5 mm
- THICKNESS : 0.06 ~ 0.09 mm
- ROLL DIAMETER : Max. \varnothing 60 mm

- ROLL CORE INNER DIAMETER : 12.5 mm ± 0.5 mm

INTERFACE

INTERFACE

- STANDARD : USB(A type)+Serial(RS-232C) Built-in

HARDWARE SPECIFICATION

POWER

- TYPE : External SMPS
- AC : 100 ~ 240Vac 50/60 Hz
- DC : 24Vdc / 2.5A

AUTO CUTTER

- TYPE : Guillotine
- LIFE : 1,000,000 cuts
- PAPER THICKNESS : 0.06 ~ 0.09 mm
- CUTTING METHOD : Partial Cut

SENSOR

- STANDARD : Paper End , Cover Open

CASH DRAWER

- 2 circuits(24V, 1A max)

RELIABILITY

- TPH LIFE : 100 km
- MCBF : 60 million Lines

TEMPERATURE

- OPERATING TEMPERATURE : 0 ~ 45°C
- STORAGE TEMPERATURE : -20 ~ 60°C

HUMIDITY

- OPERATING HUMIDITY : 35 ~ 80%
- STORAGE HUMIDITY : 10 ~ 90%

CERTIFICATION

- FCC, KCC, UL/cUL

EMULATION

EMULATION

- ESC/POS Command Compatible

DRIVER

DRIVER

- Windows Driver(10, 2012, 8, 7, 2008, VISTA, 2003, XP, 32bit & 64bit), Windows CE & Mobile Driver & SDK(CE 4.2 ~, Mobile 5.0 ~), Linux Driver, Mac Driver, OPOS Driver, JavaPOS Driver,iOS SDK, Android(2.1 ~) SDK, Windows SDK

DIMENSION

DIMENSION

- W x D x H(mm) : 120 x 182 x 106(mm)
- W x D x H(inch) : 4.7 x 7.16 x 4.17

WEIGHT

- 0.88 kg