

XP-58IIN

Function

- High speed, long life, high quality low repair rate, compatible with variety of commercial software
- Avoid order missing, protect user's benefit
- Support Chinese GB2312
- Support simplified Chinese and variety of international languages
- Support OPOS driver
- Support Windows 7、Windows 8、Linux OS driver
- Support NV logo download and trade mark printing

Printing

Printing method Direct thermal

Print width 48mm

Column capacity 384 dots/line

Printing speed 90mm/s

Interface Serial/USB

Printing paper 57.5±0.5mm×φ60mm

Line spacing 3.75mm (Adjustable by commands)

Column number 58mm paper: Font A - 32 columns/Font B - 42 columns/ Chinese,traditional Chinese - 16 columns

Character size ANK, Font A : 1.5×3.0mm (12×24 dots) Font B : 1.1×2.1mm (9×17 dots)

Chinese,traditional Chinese:3.0×3.0mm (24×24 dots)

Barcode Character

Extension character sheet PC347 (Standard Europe) 、Katakana、PC850 (Multilingual) 、PC860 (Portuguese) 、PC863 (Canadian-French)

、PC865 (Nordic) 、West Europe、Greek、Hebrew、East Europe、Iran、WPC1252、PC866 (Cyrillic#2)

、PC852 (Latin2) 、PC858、IranII、Latvian、Arabic、PT151 (1251)

Barcode types UPC-A/UPC-E/JAN13 (EAN13) /JAN8 (EAN8) / CODE39/ITF/CODABAR/CODE93/CODE128

Buffer

Input buffer 32k bytes

NV Flash 64k bytes

Power

Power adaptor Input : AC 110V/220V, 50~60Hz

Power source Output : DC 12V/2.6A

Cash drawer

Output DC 12V/1A

Physical characteristics

Weight 0.65KG

Dimensions 188x115x116mm (DxWxH)

Environmental Requirements

Work environment Temperature (0~45) humidity(10~80%)

Storage environment Temperature(-10~60°C) humidity(10~80%)

Reliability

Printer head life 50KM