

XP-P100

Specifications

Printing

Printing method	Direct thermal
Print width	48mm
Column capacity	384 dots/line
Printing speed	70mm/s
Interface	Bluetooth,USB, Rs232
Printing paper	57.5±0.5mm×φ60mm
Line spacing	3.75mm (Adjustable by commands)

Column number 58mm paper: Font A - 32 columns/Font B - 42 columns/Chinese,traditional Chinese - 16 columns

Character size ANK, Font A : 1.5×3.0mm (12×24 dots) Font B : 1.1×2.1mm (9×17 dots) Chinese,traditional Chinese:3.0×3.0mm (24×24 dots)

Cutter

Auto cutter	Full or partial (Optional)
-------------	-----------------------------

Barcode Character

Extension character sheet PC347 (Standard Europe) 、Katakana、PC850 (Multilingual) 、PC860 (Portuguese) 、PC863 (Canadian-French) 、PC865 (Nordic) 、 West Europe、Greek、Hebrew、East Europe、Iran、WPC1252、PC866 (Cyrillic#2) 、PC852 (Latin2) 、PC858、IranII、Latvian、Arabic、PT151 (1251)

Barcode types UPC-A/UPC-E/JAN13 (EAN13) /JAN8 (EAN8) /CODE39/ITF/CODABAR/CODE93/CODE128

Buffer

Input buffer	32k bytes
NV Flash	64k bytes

Power

Power adaptor Input : AC 110V/220V, 50~60Hz

Power source Output : DC 12V/2.6A

Battery 2000m Ah

Output DC 12V/1A

Physical characteristics

Weight 1.18KG

Dimensions 191x132x128mm (DxWxH)

Environmental Requirements

Work environment Temperature (0~45) humidity(10~80%)

Storage environment Temperature(-10~60°C) humidity(10~80%)

Reliability

Cutter life 500 thousand cuts

Printer head life 50KM