

# XP-C260L

Thermal Receipt Printer (Kitchen Solution)

## Key features

- Support sound and light alarm function
- Louder beeper design, good choice for kitchen
- 2048k bytes input buffer avoid order missing
- Wall mount installation available
- Support QR Code, PDF417.



POS Printer



## Specifications

Model	XP-C260L
Printing method	Direct thermal
Printing speed	260mm/s
Paper width	79.5 ± 0.5mm
Paper diameter	80mm
Paper thickness	0.06~0.08mm
Column capacity	576 dots/line 512 dots/line
Line space	3.75mm(changeable using commands)
Character size	ANK, Font A: 12×24 dots Font B: 9×17 dots simplified/traditional Chinese: 24×24 dots
Bar code	UPC-A/UPC-E/JAN13 (EAN13) /JAN8 (EAN8) /CODABAR/ITF/CODE39/CODE93/CODE128 QR CODE/PDF417
Code page	Pc347(Standard Europe) \ Katakana \ PC850(Multilingual) \ PC860(Portuguese) \ Pc863(Canadian-French) \ PC865(Nordic) \ West Europe \ Greek, Hebrew, East Europe \ Iran \ WPC1252 \ PC866(Cyrillic#2) \ PC852(Latin2) \ Pc858 \ IranII \ Latvian \ Arabic \ Pt151(1251)
NV FLASH	256K Bytes
Input buffer	2048K Bytes
Power supply	DC 24V ±2.5A
Cash drawer control	DC 24V ±1A
Interface	Serial+USB+Lan/Wifi+USB/Bluetooth+USB
Auto cutter	Partial
Reliability	Printing head life: 100 km Auto cutter life: 1 million cuts
Working environment	Temperature (0~45°c), humidity(10~80%)
Storage environment	Temperature (-10~60°c), humidity(10~90%)
Drivers	Win 9X/Win ME/Win 2000/Win 2003/Win NT/Win XP/Win Vista/Win 7/Win 8/Win 10/Linux/OPOS
Command	Compatible with ESC/POS
Gross weight	1.66 kg
Dimension	193 × 145 × 139mm (D × W × H)