

● DOT IMPACT PRINTER

SLK-D10

- Selectable Roll type or Sprocket type
- Compact yet durable and stable
- 3.5Lines/sec speed printing
- Standard interfaces : Serial, Parallel(25pin/36pin)
- Dual interface (optional) : Serial + MSR
- Built-in buzzer (optional)



INTERFACE



TYPE



Roll Type



Sprocket Type

● SPECIFICATION

ITEM	TYPE	
MODEL	SLK-D10	
PRINTING	METHOD	9-pin Serial Dot Impact Matrix
	DIRECTION	Bi-directional (with logical seeking)
	SPEED	3.5 lines/sec
	WIDTH	63.5mm / 57.2mm
	LINE SPACING	n/144inch
	RESOLUTION	160DPI / 80DPI
	NO. OF COLUMNS	TM-U200 Emulation : 42/35, 40/33 Other Emulation : 40/33
PAPER	NO. OF TOTAL DOTS	400 dots/line
	FONT SIZE	7x9, 9x9 / 5x9, 7x9
	TYPE	Roll paper / Sprocket
	WIDTH	76.2mm / 89mm, 76.2mm
PAPER	THICKNESS	72mm
	ROLL DIAMETER	Original + 2copies
INK RIBBON	ERC-23 Compatible (Black, Purple)	
RELIABILITY	PRINT HEAD	18million lines
	MCB	120million characters
INTERFACE	Serial(25pin), Parallel (25pin, 36pin), Combo(Serial+MSR)	
EMULATION	TM-U200, TM-U300, iDP-3540, SP200 Command Compatible	
DRIVER	Windows Driver(2012, 8, 7, 2008, VISTA, 2003, XP, 32bit & 64bit), Linux, OPOS, JavaPOS, WEPOS Driver	
POWER	TYPE	External SMPS
	AC	100 ~ 240Vac 50/60 Hz
	DC	24Vdc / 2.5A
TEMPERATURE	OPERATION	0 ~ 45°C
	STORAG	-20 ~ 60°C
DIMENSION	162mm x 282mm x 138 mm (W x D x H)	
WEIGHT	1.26kg	
COLOR	Dark grey, Ivory	

