

POS PRINTER




SLK-TL202 II

- Energy star qualified for power efficiency
- High speed printing : 220mm/sec
- Paper width adjustable 50~82.5mm
- ESC/POS command compatible
- Accessories : Melody box, spillproof cover
- Wall mount installation available




www.miniprinter.com

APPLICATIONS



EASY-LOAD DESKTOP THERMAL POS PRINTER

SLK-TL202 II



MODEL		SLK-TL202 II
PRINTING	METHOD	Direct Thermal
	SPEED	Max. 220mm/sec
	WIDTH	72mm(512 Dots/Line)
	RESOLUTION	180DPI
PAPER	TYPE	Thermal Receipt Paper / Linerless(Optional)
	WIDTH	50mm ~ 82.5mm
	THICKNESS	0.06mm ~ 0.09mm
	ROLL DIAMETER	Max. ø 80.0mm
RELIABILITY	TPH LIFE	160km
	MCBF	60,000,000Lines
AUTO CUTTER		1,800,000cuts(Guillotine)
SENSOR	STANDARD	Paper End, Paper Low, Cover Open
	OPTION	Black Mark
INTERFACE		USB (B type) + Serial Built-in
EMULATION		ESC/POS Command Compatible
DRIVER		Windows Driver(10, 2012, 8, 7, 2008, VISTA, 2003, XP, 32bit & 64bit), Windows CE & Mobile Driver & SDK(CE 4.2 ~, Mobile 5.0 ~), Linux Driver, Mac Driver, OPOS Driver, JavaPOS Driver, iOS SDK, Android(2.1 ~) SDK, Windows SDK
POWER	TYPE	External SMPS
	AC	100 ~ 240Vac 50/60 Hz
	DC	24Vdc / 1.75A
TEMPERATURE	OPERATION	0 ~ 45°C
	STORAGE	-20 ~ 60°C
DIMENSION		152 x 204 x150 mm (W x D x H)
WEIGHT		1.7kg
COLOR		Cool grey, Ivory

INTERFACE



ACCESSORY



Spill proof cover



Melody box

• All specification and desings are subject to change without notice.



SEWOO TECH Co., Ltd.

28-6, Gajangsaneopdong-ro, Osan-si, Gyeonggi-do, 447-210 Republic of Korea
 T. +82-31-8077-5000 F. +82-31-459-8880
 www.miniprinter.com

