

HIGH PERFORMANCE THERMAL PRINTER WITH MSR

# POS PRINTER

## SLK-T22

- 1, 2 track or 2, 3 track MSR
- Support ASB(Auto status back)
- Paper end sensor, Cover open sensor, Paper low sensor, Black mark sensor(Optional)



### INTERFACE



### MSR



### SPECIFICATION

ITEM	TYPE	
MODEL	SLK-T22	
PRINTING	METHOD	Direct Thermal
	SPEED	150mm/sec
	WIDTH	72mm(512Dots/Line)
	RESOLUTION	180DPI
PAPER	TYPE	Thermal Paper
	WIDTH	50mm ~ 82.5mm
	THICKNESS	0.06mm ~ 0.09mm
	ROLL DIAMETER	Max. ø 80.0mm
	ROLL CORE INNER	12.5mm ± 0.5mm
RELIABILITY	TPH LIFE	160km
	MCBF	60,000,000Lines
AUTO CUTTER	1,500,000cuts(Guillotine)	
SENSOR	Paper End, Paper Low, Cover Open, Black Mark Sensor(Optional)	
INTERFACE	Serial, Parallel, Ethernet, USB, WII-fi(802.11b), Combo(Serial+USB)	
EMULATION	ESC/POS Command Compatible	
DRIVER	Window Printer Driver(7, XP, 2000, 2003, VISTA), WEPOS, OPOS, Linux, JavaPOS	
POWER	TYPE	External SMPS
	AC	100 ~ 240Vac 50/60 Hz
	DC	24Vdc / 2.5A
TEMPERATURE	OPERATION	0 ~ 45°C
	STORAGE	-20 ~ 60°C
DIMENSION	152mm x 204mm x 150 mm (W x D x H)	
WEIGHT	1.7kg	
COLOR	Cool grey, Ivory	

