

XP-58IIA

Thermal Receipt Printer

POS Printer

Key features

- Outstanding functions, Strong stability
- Support Linux & Windows system
- Support OPOS driver
- Avoid order missing
- Support simplified/traditional Chinese, Japanese, Korean and many other international Languages



Specifications

Model	XP-58IIA
Printing method	Direct thermal
Printing speed	90mm/s
Paper width	57.5 ± 0.5mm
Paper diameter	60mm
Paper thickness	0.06-0.08mm
Column capacity	384 dots/line
Line space	3.75mm (changeable using commands)
Character size	ANK, Font A: 12×24 dots Font B: 9×17 dots simplified/traditional Chinese: 24×24 dots
Bar code	UPC-A/UPC-E/JAN13 (EAN13) /JAN8 (EAN8) /CODABAR/ITF/CODE39/CODE93/CODE128
Code page	PC347 (Standard Europe), Katakana, PC850 (Multilingual), PC860 (Portuguese), PC863 (Canadian-French), PC865 (Nordic), West Europe, Greek, Hebrew, East Europe, Iran, WPC1252, PC866 (Cyrillic#2), PC852 (Latin2), PC858, IranII, Latvian, Arabic, PT151 (1251)
NV FLASH	64K Bytes
Input buffer	32K Bytes
Power supply	DC 12V = 2.6A
Cash drawer control	DC 12V = 1A
Interface	Parallel/Serial/USB/Lan
Reliability	Printing head life: 50 km
Working environment	Temperature (0-45°C), humidity(10-80%)
Storage environment	Temperature (-10-60°C), humidity(10-90%)
Drivers	Win 9X/Win ME/Win 2000/Win 2003/Win NT/Win XP/Win Vista/Win 7/Win 8/Win 8.1/Linux
Command	Compatible with ESC/POS
Gross weight	0.82 kg
Dimension	215×135×107.5mm D(xW x H)