

XP-58IIL

Thermal Receipt Printer

Key features

- High speed, long lifetime, high quality
- Outstanding functions, Strong stability
- Support Linux & Windows system
- Support Chinese GB2312
- Avoid order missing
- Compatible with ESC/POS commands



Specifications

Model	XP-58IIL
Printing method	Direct thermal
Printing speed	90mm/s
Paper width	57.5 ± 0.5mm
Paper diameter	60mm
Paper thickness	0.06~0.08mm
Column capacity	384 dots/line
Line space	3.75mm (changeable using commands)
Character size	ANK, Font A: 12×24 dots Font B: 9×17 dots simplified/traditional Chinese: 24×24 dots
Bar code	UPC-A/UPC-E/JAN13 (EAN13) /JAN8 (EAN8) /CODABAR/ITF/CODE39/CODE93/CODE128
Code page	PC347 (Standard Europe) 、Katakana、PC850 (Multilingual) 、PC860 (Portuguese) 、PC863 (Canadian-French) 、PC865 (Nordic) 、West Europe、Greek、Hebrew、East Europe、Iran、WPC1252、PC866 (Cyrillic#2) 、PC852 (Latin2) 、PC858、IranII、Latvian、Arabic、PT151 (1251)
NV FLASH	64K Bytes
Input buffer	32K Bytes
Power supply	DC 12V± 2.6A
Cash drawer control	DC 12V± 1A
Interface	USB/USB+Bluetooth
Auto cutter	-----
Reliability	Printing head life: 50 km
Working environment	Temperature (0~45°C), humidity(10~80%)
Storage environment	Temperature (-10~60°C), humidity(10~90%)
Drivers	Win 9X/Win ME/Win 2000/Win 2003/Win NT/Win XP/Win 7/Win 8/Win 10/Linux/Android/IOS
Command	Compatible with ESC/POS
Gross weight	0.79 kg
Dimension	185×132×110mm (D×W×H)