

XP-7645III

Impact Dot Matrix Printer

Key features

- Freshness outerside design, easy operation
- GB18030 simplified Chinese, traditional Chinese, buyers languages
- Black mark orientation, support invoice printing function
- Various interfaces, multiple choices
- 100MB Ethernet interface connection transfer data efficiently
- Avoid order missing



Specifications

Model	XP-7645III
Printing method	9-Pin serial impact dot-matrix printing
Printing speed	4.5 line/sec
Paper width	75.5 ± 0.5mm
Paper diameter	80mm
Paper thickness	0.06~0.08mm
Column capacity	400 dots/line
Line space	4.23mm (changeable using commands)
Character size	ANK, Font A: 9x9 dots Font B: 7x9 dots Simplified/traditional Chinese: 16x16 dots
Black mark detection	Support
Code page	PC347 (Standard Europe)、Katakana、PC850 (Multilingual)、PC860 (Portuguese)、 PC863 (Canadian-French)、PC865 (Nordic)、West Europe, Greek, Hebrew, East Europe, Iran, WPC1252, PC866 (Cyrillic#2)、PC852 (Latin2)、PC858, IranII, Latvian, Arabic, PT151 (1251)
Input buffer	32 K Bytes
Power supply	DC 24V ± 2.5A
Cash drawer control	DC 24V ± 1A
Interface	Parallel/Serial/Lan/USB
Auto cutter	-----
Reliability	Printing head life: 10 Million Lines
Working environment	Temperature (0~45°C), humidity(10~80%)
Storage environment	Temperature (-10~60°C), humidity(10~90%)
Drivers	Win 9X/Win ME/Win 2000/Win 2003/Win NT/Win XP/Win Vista/Win 7/Win 8/Win 8.1/Linux
Command	Compatible with ESC/POS
Gross weight	1.36 kg
Dimension	230 x 150 x 130mm D(W x H)