

XP-76II+C

Impact Dot Matrix Printer

Dot Matrix Printer

Key features

- Support GB18030
- Three-ply capable
- Black mark orientation
- Bi-directional printing



Specifications

Model	XP-76II+C
Printing method	9-Pin serial impact dot-matrix printing
Printing speed	4.5 line/sec
Paper width	75.5 ± 0.5mm
Paper diameter	80mm
Paper thickness	0.06~0.08mm
Column capacity	400 dots/line
Line space	4.23mm (changeable using commands)
Character size	ANK, Font A: 9×9 dots Font B: 7×9 dots Simplified/traditional Chinese: 16×16 dots
Black mark detection	Support
Code page	PC347 (Standard Europe)、Katakana、PC850 (Multilingual)、PC860 (Portuguese)、PC863 (Canadian-French)、PC865 (Nordic)、West Europe、Greek、Hebrew、East Europe、Iran、WPC1252、PC866 (Cyrillic#2)、PC852 (Latin2)、PC858、Iranli、Latvian、Arabic、PT151 (1251)
Input buffer	32 K Bytes
Power supply	DC 24V ± 2.5A
Cash drawer control	DC 24V ± 1A
Interface	Parallel/Serial/Lan/USB
Auto cutter	Full or partial (optional)
Reliability	Printing head life: 10 Million Lines Auto cutter life: 1 million cuts
Working environment	Temperature (0~45°C), humidity(10~80%)
Storage environment	Temperature (-10~60°C), humidity(10~90%)
Drivers	Win 9X/Win ME/Win 2000/Win 2003/Win NT/Win XP/Win Vista/Win 7/Win 8/Win 8.1/Linux
Command	Compatible with ESC/POS
Gross weight	1.36 kg
Dimension	230 x 146 x 145mm D(W x H)