

XP-C230 / C260K

Thermal Receipt Printer

Key features

- Top paper loading
- Avoid order missing
- Dual interface serial+usb or full ports
- Support black mark orientation
- ESC/POS command compatible



Windows 7



Windows 8



Windows 10



Linux



Specifications

Model	XP-C230	XP-C260K
Printing method	Direct thermal	
Printing speed	230mm/s	260mm/s
Paper width	79.5 ± 0.5mm	
Paper diameter	80mm	
Paper thickness	0.06~0.08mm	
Column capacity	576 dots/line 512 dots/line	
Line space	3.75mm (changeable using commands)	
Character size	ANK, Font A: 12×24 dots Font B: 9×17 dots simplified/traditional Chinese: 24x24 dots	
Bar code	UPC-A/UPC-E/JAN13 (EAN13) /JAN8 (EAN8) /CODABAR/ITF/CODE39/CODE93/CODE128 QR CODE/PDF417	
Code page	PC347 (Standard Europe) 、Katakana、PC850 (Multilingual) 、PC860 (Portuguese) 、 PC863 (Canadian-French) 、PC865 (Nordic) 、West Europe、Greek、Hebrew、East Europe、 Iran、WPC1252、PC866 (Cyrillic#2) 、PC852 (Latin2) 、PC858、IranII、Latvian、Arabic、 PT151 (1251)	
NV FLASH	256K Bytes	
Input buffer	64K Bytes	2048K Bytes
Power supply	DC 24V ≍ 2.5A	
Cash drawer control	DC 24V ≍ 1A	
Interface	Parallel/USB+Serial/Lan	Serial+USB+Lan
Auto cutter	Partial	
Reliability	Printing head life: 100 km Auto cutter life: 1 million cuts	
Working environment	Temperature (0~45°C), humidity(10~80%)	
Storage environment	Temperature (-10~60°C), humidity(10~90%)	
Drivers	Win 9X/Win ME/Win 2000/Win 2003/Win NT/Win XP/Win Vista/Win 7/Win 8/Win 10/Linux/OPOS	
Command	Compatible with ESC/POS	
Gross weight	1.52 kg	
Dimension	200 × 140 × 140mm (D × W × H)	