

XP-D300M

Front Paper Loading Printer

Key features

- Vertical printing and desktop printing supported
- Support 58mm and 80mm paper width
- High Speed Printing : 300mm/s
- Wall mount installation available
- Support various drivers



POS Printer



Specifications

Model	XP-D300M
Printing method	Direct thermal
Printing speed	300mm/s
Paper width	57.5 ± 0.5mm 79.5 ± 0.5mm
Paper diameter	80mm
Paper thickness	0.06~0.08mm
Column capacity	384mm dots/ line (58mm) 576 dots/line 512 dots/line (80mm)
Line space	3.75mm (changeable using commands)
Character size	ANK, Font A: 12×24 dots Font B: 9×17 dots simplified/traditional Chinese: 24×24 dots
Bar code	UPC-A/UPC-E/JAN13 (EAN13) /JAN8 (EAN8) /CODABAR/ITF/CODE39/CODE93/CODE128 QR CODE
Code page	PC347 (Standard Europe) 、Katakana、PC850 (Multilingual) 、PC860 (Portuguese) 、PC863 (Canadian-French) 、PC865 (Nordic) 、West Europe、Greek、Hebrew、East Europe、Iran、WPC1252、PC866 (Cyrillic#2) 、PC852 (Latin2) 、PC858、IranII、Latvian、Arabic、PT151 (1251)
NV FLASH	256K Bytes
Input buffer	2048K Bytes
Power supply	DC 24V ≒2.5A
Cash drawer control	DC 24V ≒ 1A
Interface	Serial+USB+Lan
Auto cutter	Partial
Reliability	Printing head life: 100 km Auto cutter life: 1 million cuts
Working environment	Temperature (0~45°C), humidity(10~80%)
Storage environment	Temperature (-10~60°C), humidity(10~90%)
Drivers	Win 9X/Win ME/Win 2000/Win 2003/Win NT/Win XP/Win Vista/Win 7/Win 8/Win 10/Linux/OPOS
Command	Compatible with ESC/POS
Gross weight	1.44 kg
Dimension	144.5 × 146 × 188.5mm (D × W × H)