

XP-F76EC

Dot Matrix Printer

Key features

- Support international languages
- Easy paper loading
- 2-color printing
- ESC/POS command compatible
- Imported cutter and mechanism



Windows 7

Windows 8

Windows 10

Linux

Specifications

Model	XP-F76EC
Printing method	Dot matrix printing
Printing speed	4.5 line/sec
Paper width	75.5 ± 0.5mm
Paper diameter	80mm
Paper thickness	0.06~0.08mm
Column capacity	400 dots/line
Line space	4.23mm (changeable using commands)
Character size	ANK, Font A: 9x9 dots Font B: 7x9 dots Simplified/traditional Chinese: 16x16 dots
Black mark detection	Support
Code page	PC347 (Standard Europe)、Katakana、PC850 (Multilingual)、PC860 (Portuguese)、PC863 (Canadian-French)、PC865 (Nordic)、West Europe、Greek、Hebrew、East Europe、Iran、WPC1252、PC866 (Cyrillic#2)、PC852 (Latin2)、PC858、IranII、Latvian、Arabic、PT151 (1251)
Input buffer	32 K Bytes
Power supply	DC 24V ± 2.5A
Cash drawer control	DC 24V ± 1A
Interface	Serial+USB+Lan
Auto cutter	Partial
Reliability	Printing head life: 10 Million Lines Auto cutter life: 1 Million cuts
Working environment	Temperature (0~45°C), humidity(10~80%)
Storage environment	Temperature (-10~60°C), humidity(10~90%)
Drivers	Win 9X/Win ME/Win 2000/Win 2003/Win NT/Win XP/Win Vista/Win 7/Win 8/Win 10/Linux/OPOS
Command	Compatible with ESC/POS
Gross weight	2.2 kg
Dimension	247 × 156 × 143mm (D × W × H)