

XP-H260L

Thermal Receipt Printer

POS Printer

Key features

- Support sound and light alarm function
- Louder beeper design, good choice for kitchen
- Wall mount installation available
- Support QR CODE Printing



Windows 7



Windows 8



Windows 10



Linux



Specifications

Model	XP-H260L
Printing method	Direct thermal
Printing speed	260mm/s
Paper width	79.5 ± 0.5mm
Paper diameter	80mm
Paper thickness	0.06~0.08mm
Column capacity	576 dots/line 512 dots/line
Line space	3.75mm (changeable using commands)
Character size	ANK, Font A: 12×24 dots Font B: 9×17 dots simplified/traditional Chinese: 24×24 dots
Bar code	UPC-A/UPC-E/JAN13 (EAN13)/JAN8 (EAN8)/CODABAR/ITF/CODE39/CODE93/CODE128 QR CODE
Code page	PC347 (Standard Europe)、Katakana、PC850 (Multilingual)、PC860 (Portuguese)、PC863 (Canadian-French)、PC865 (Nordic)、West Europe、Greek、Hebrew、East Europe、Iran、WPC1252、PC866 (Cyrillic#2)、PC852 (Latin2)、PC858、IranII、Latvian、Arabic、PT151 (1251)
NV FLASH	256K Bytes
Input buffer	64K Bytes
Power supply	DC 24V ∓ 2.5A
Cash drawer control	DC 24V ∓ 1A
Interface	Serial+USB
Auto cutter	Full/Partial(optional)
Reliability	Printing head life: 100 km Auto cutter life: 1 million cuts
Working environment	Temperature (0~45°C), humidity(10~80%)
Storage environment	Temperature (-10~60°C), humidity(10~90%)
Drivers	Win 9X/Win ME/Win 2000/Win 2003/Win NT/Win XP/Win Vista/Win 7/Win 8/Win 8.1/Linux/OPOS
Command	Compatible with ESC/POS
Gross weight	1.81 kg
Dimension	193.3 × 145 × 144mm (D × W × H)