

# XP-Q80I

Thermal Receipt Printer

## Key features

- 200mm/s High speed printing
- Lan/USB+Serial interfaces together
- Change IP through Web or Serial port
- Support Linux, Win 8.1 system



POS Printer



Windows 7



Windows 8



Windows 10



Linux



## Specifications

| Model               | XP-Q80I  |
|---------------------|--|
| Printing method     | Direct thermal   |
| Printing speed      | 200mm/s  |
| Paper width         | 79.5 ± 0.5mm   |
| Roll paper          | 80mm   |
| Paper thickness     | 0.06-0.08mm  |
| Column capacity     | 576 dots/line 512 dots/line (80mm)   |
| Line space          | 3.75mm (changeable using commands)   |
| Character size      | ANK, Font A: 12×24 dots<br>Font B: 9×17 dots<br>simplified/traditional Chinese: 24×24 dots   |
| Bar code            | UPC-A/UPC-E/JAN13 (EAN13) /JAN8 (EAN8) /CODABAR/ITF/CODE39/CODE93/CODE128  |
| Code page           | PC347 (Standard Europe)、Katakana、PC850 (Multilingual)、PC860 (Portuguese)、PC863 (Canadian-French)、PC865 (Nordic)、West Europe、Greek、Hebrew、East Europe、Iran、WPC1252、PC866 (Cyrillic#2)、PC852 (Latin2)、PC858、IranII、Latvian、Arabic、PT151 (1251) |
| NV FLASH            | 256K Bytes   |
| Input buffer        | 64K Bytes  |
| Power supply        | DC 24V ± 2.5A  |
| Cash drawer control | DC 24V ± 1A  |
| Interface           | USB+Serial/Lan   |
| Auto cutter         | Full/Partial(optional)   |
| Reliability         | Printing head life: 100 km Auto cutter life: 1 million cuts  |
| Working environment | Temperature (0-45°C), humidity(10-80%)   |
| Storage environment | Temperature (-10-60°C), humidity(10-90%)   |
| Drivers             | Win 9X/Win ME/Win 2000/Win 2003/Win NT/Win XP/Win Vista/Win 7/Win 8/Win 8.1/Linux/OPOS   |
| Command             | Compatible with ESC/POS  |
| Gross weight        | 1.1 kg   |
| Dimension           | 195 × 140 × 142.5mm D(× W × H)   |