

XP-T58H

Thermal Receipt Printer

Key features

- High speed, long lifetime, high quality
- Outstanding functions, Strong stability
- Support Linux & Windows system
- Support OPOS driver
- Support Chinese GB18030
- Avoid order missing
- Compatible with ESC/POS commands



Specifications

Model	XP-T58H
Printing method	Direct thermal
Printing speed	120mm/s
Paper width	57.5 ± 0.5mm
Paper diameter	60mm
Paper thickness	0.06~0.08mm
Column capacity	384 dots/line
Line space	3.75mm (changeable using commands)
Character size	ANK, Font A: 12×24 dots Font B: 9×17 dots simplified/traditional Chinese: 24×24 dots
Bar code	UPC-A/UPC-E/JAN13 (EAN13) /JAN8 (EAN8) /CODABAR/ITF/CODE39/CODE93/CODE128
Code page	PC347 (Standard Europe) , Katakana, PC850 (Multilingual) , PC860 (Portuguese) , PC863 (Canadian-French) , PC865 (Nordic) , West Europe, Greek, Hebrew, East Europe, Iran, WPC1252, PC866 (Cyrillic#2) , PC852 (Latin2) , PC858, Iran11, Latvian, Arabic, PT151 (1251)
NV FLASH	64K Bytes
Input buffer	32K Bytes
Power supply	DC 12V= 2.6A
Cash drawer control	DC 12V= 1A
Interface	Parallel/Serial/USB/Lan
Reliability	Printing head life: 50 km Auto cutter life: 500 thousand cuts
Working environment	Temperature (0~45°C), humidity(10~80%)
Storage environment	Temperature (-10~60°C), humidity(10~90%)
Drivers	Win 9X/Win ME/Win 2000/Win 2003/Win NT/Win XP/Win Vista/Win 7/Win 8/Win 8.1/Linux
Command	Compatible with ESC/POS
Gross weight	0.88 kg
Dimension	180 × 135 × 135mm D(×W × H)