

XP-T58KC

Thermal Receipt Printer

Key features

- Auto cutter (optional)
- Big gear, Long-life, Durable
- High printing speed 120mm/sec, High Reliability
- USB+Bluetooth wireless connection
- Support Chinese GB 18030
- Compatible with ESC/POS commands



Specifications

Model	XP-T58KC
Printing method	Direct thermal
Printing speed	120mm/s
Paper width	57.5 ± 0.5mm
Paper diameter	60mm
Paper thickness	0.06~0.08mm
Column capacity	384 dots/line
Line space	3.75mm (changeable using commands)
Character size	ANK, Font A: 12×24 dots Font B: 9×17 dots simplified/traditional Chinese: 24×24 dots
Bar code	UPC-A/UPC-E/JAN13 (EAN13) /JAN8 (EAN8) /CODABAR/ITF/CODE39/CODE93/CODE128
Code page	PC347 (Standard Europe)、Katakana、PC850 (Multilingual)、PC860 (Portuguese)、PC863 (Canadian-French)、PC865 (Nordic)、West Europe、Greek、Hebrew、East Europe、Iran、WPC1252、PC866 (Cyrillic#2)、PC852 (Latin2)、PC858、Iranll、Latvian、Arabic、PT151 (1251)
NV FLASH	64K Bytes
Input buffer	32K Bytes
Power supply	DC 12V± 2.6A
Cash drawer control	DC 12V± 1A
Interface	Parallel/Serail/USB/Lan/USB+Bluetooth
Auto cutter	Partial
Reliability	Printing head life: 50 km Auto cutter life: 500 thousand cuts
Working environment	Temperature (0~45°C), humidity(10~80%)
Storage environment	Temperature (-10~60°C), humidity(10~90%)
Drivers	Win 9X/Win ME/Win 2000/Win 2003/Win NT/Win XP/Win Vista/Win 7/Win 8/Win 10/Linux
Command	Compatible with ESC/POS
Gross weight	1.10 kg
Dimension	199 × 132 × 111.5mm (D × W × H)