

XP-N230I

Thermal Receipt Printer

Key features

- Easy load design
- High speed printing graphic and text
- Support international languages.
- Support Linux, Windows systems and OPOS
- ESC/POS compatible
- Support 256K NV logo download and print



Windows 7

Windows 8

Windows 10

Linux

Specifications

Model	XP-N230I
Printing method	Direct therma
Print width	76mm
Column capacity	576 dots/line 512 dots/line
Printing speed	230mm/s
Interface	Parallel/Serial/USB/Lan
Printing paper	79.5±0.5mm×φ80mm
Line spacing	3.75mm (Adjustable by commands)
Column number	80mm paper: Font A - 42 columns or 48 columns/Font B - 56 columns or 64 columns/ Chinese,traditional Chinese - 21 columns or 24 columns
Character size	ANK · Font A:1.5×3.0mm(12×24 dots) Font B:1.1×2.1mm(9×17 dots) Chinese,traditional Chinese:3.0×3.0mm(24×24 dots)
Extension character sheet	Pc347(Standard Europe), Katakana, PC850(Multilingual), PC860(Portuguese), Pc863(Canadian-French), PC865(Nordic), West Europe, Greek, Hebrew, East Europe, Iran, WPC1252, PC866(Cyrillic#2)PC852(Latin2), PC858, IranII, Latvian, Arabic, PT151(1251) UPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)/CODE39/ITF/CODABAR/CODE93/CODE128
Barcode types	
Input buffer	64k bytes
NV Flash	256k bytes
Power adaptor	Input:AC 110V/220V, 50~60Hz
Power source	Output:DC 24V/2.5A
Cash drawer output	DC 24V/1A
Weight	1.48KG
Dimensions	190×145×153mm (D×W×H)
Work environment	Temperature (0~45) humidity(10~80%)
Storage environment	Temperature(-10~60℃)humidity(10~80%)
Printer head life	100KM